

MATERIAL SAFETY DATA SHEET (REACH)

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830

Revision: 27/09/2016

Page 1 / 11

**REVESTIMIENTO ELÁSTICO FOTO-RETICULABLE MACYFILM**
Code: 50450

Version: 3 Revision: 27/09/2016

Previous revision: 21/09/2016

Date of printing: 27/09/2016

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 **PRODUCT IDENTIFIER:** REVESTIMIENTO ELÁSTICO FOTO-RETICULABLE MACYFILM
Code: 50450
- 1.2 **RELEVANT IDENTIFIED USES AND USES ADVISED AGAINST:**
Intended uses (main technical functions): ☐ Industrial ☒ Professional ☒ Consumers
Decorative paint.
Sectors of use:
Consumer uses (SU21).
Uses advised against:
None. As there is not classified as dangerous, this product can be used in ways other than the identified uses, but all uses have to be consistent with the safety guidelines provided.
Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006:
Not restricted.
- 1.3 **DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:**
PINTURAS MACY, S.A.
Ctra. Nacional 301, Km. 212,8 - E-02630 - La Roda (Albacete)
Phone: +34 967 440712 - Fax: +34 967 442819
E-mail address of the person responsible for the safety data sheet:
e-mail: laborato102@pinturas-macy.com
- 1.4 **EMERGENCY TELEPHONE NUMBER:** +34 967 440712 (8:00-13:00 / 16:00-20:00 h.) (working hours)

SECTION 2 : HAZARDS IDENTIFICATION

- 2.1 **CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:**
This product is not classified as dangerous. in accordance with Regulation (EC) No. 1272/2008~605/2014 (CLP)

Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.

Note: This product does not require a material safety data sheet (MSDS) according to the Regulation (EC) no. 2015/830. When used as recommended or under ordinary conditions, it should not present a physicochemical, health safety or environmental hazard. However, an MSDS can be provided as a courtesy in response to a customer request.
- 2.2 **LABEL ELEMENTS:**
This product does not require pictograms, in accordance with Regulation (EC) No. 1272/2008~605/2014 (CLP)
Hazard statements:
None.
Precautionary statements:
P102 Keep out of reach of children.
P271 Use only outdoors or in a well-ventilated area.
P280B Wear protective gloves and eye protection .
P273 Avoid release to the environment.
Supplementary statements:
EUH208 Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one, mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1). May produce an allergic reaction.
EUH210 Safety data sheet available on request.
EUB174 Contains a preservative/slimicide to protect the film. See information supplied by the manufacturer.
Hazardous ingredients:
None.
- 2.3 **OTHER HAZARDS:**
Hazards which do not result in classification but which may contribute to the overall hazards of the mixture:
Other physicochemical hazards: No other relevant adverse effects are known.
Other adverse human health effects: No other relevant adverse effects are known.
Other negative environmental effects: Does not contain substances that fulfil the PBT/vPvB criteria.



REVESTIMIENTO ELÁSTICO FOTO-RETICULABLE MACYFILM
Code: 50450

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.1

SUBSTANCES:

Not applicable (mixture).

3.2

MIXTURES:

This product is a mixture.

Chemical description:

Solution of acrylic copolymer in aqueous media.

HAZARDOUS INGREDIENTS:

Substances taking part in a percentage higher than the exemption limit:

None

Impurities:

Does not contain other components or impurities which will influence the classification of the product.

Stabilizers:

None

Reference to other sections:

For more information, see sections 8, 11 and 12.

SUBSTANCES OF VERY HIGH CONCERN (SVHC):

List updated by ECHA on 20/06/2016.

Substances SVHC subject to authorisation, included in Annex XIV of Regulation (EC) no. 1907/2006:

None

Substances SVHC candidate to be included in Annex XIV of Regulation (EC) no. 1907/2006:

None

PERSISTENT, BIOACCUMULABLE AND TOXIC PBT, OR VERY PERSISTENT AND VERY BIOACCUMULABLE VPVB SUBSTANCES:

Does not contain substances that fulfill the PBT/vPvB criteria.



REVESTIMIENTO ELÁSTICO FOTO-RETICULABLE MACYFILM
Code: 50450

SECTION 4 : FIRST AID MEASURES
4.1 DESCRIPTION OF FIRST-AID MEASURES:


Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures
<u>Inhalation:</u>	Normally does not produce symptoms.	Should there be any symptoms, transfer the person affected to the open air.
<u>Skin:</u>	Normally does not produce symptoms.	Remove contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser. Do not use solvents or thinners.
<u>Eyes:</u>	Normally does not produce symptoms.	Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water, holding the eyelids apart. If irritation persists, consult a physician.
<u>Ingestion:</u>	If swallowed in high doses, may cause gastrointestinal disturbances.	If swallowed, seek immediate medical attention. Do not induce vomiting, due to the risk of aspiration. Keep the patient at rest.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

The main symptoms and effects are indicated in sections 4.1 and 11

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:

Notes to physician: Treatment should be directed at the control of symptoms and the clinical condition of the patient.

Antidotes and contraindications: Specific antidote not known.

SECTION 5 : FIRE-FIGHTING MEASURES
5.1 EXTINGUISHING MEDIA:

In the case of fire in the surroundings, all extinguishing agents are allowed.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products may be a hazard to health.

5.3 ADVICE FOR FIREFIGHTERS:

Special protective equipment: Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or not used, combat fire from a sheltered position or at a safe distance. The standard EN469 provides a basic level of protection for chemical incidents.
Other recommendations: Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.

SECTION 6 : ACCIDENTAL RELEASE MEASURES
6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Avoid direct contact with this product. The floor may become slippery.

6.2 ENVIRONMENTAL PRECAUTIONS:

Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:

Contain and mop up spills with absorbent materials (sawdust, earth, sand, vermiculite, diatomaceous earth, etc.). Avoid use of solvents. Keep the remains in a closed container.

6.4 REFERENCE TO OTHER SECTIONS:

For contact information in case of emergency, see section 1.
For information on safe handling, see section 7.
For exposure controls and personal protection measures, see section 8.
For subsequent waste disposal, follow the recommendations in section 13.



REVESTIMIENTO ELÁSTICO FOTO-RETICULABLE MACYFILM
Code: 50450

SECTION 7 : HANDLING AND STORAGE

- 7.1** PRECAUTIONS FOR SAFE HANDLING:
Comply with the existing legislation on health and safety at work.
General recommendations:
Avoid any type of leakage or escape. Keep the container tightly closed.
Recommendations for the prevention of fire and explosion risks:
Although due its low flammability does not represent a serious risk of fire, all type of measures should be taken in order to avoid any possibility of ignition.
Recommendations for the prevention of toxicological risks:
Do not eat, drink or smoke in application and drying areas. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8.
Recommendations for the prevention of environmental contamination:
It is not considered a danger to the environment. In the case of accidental spillage, follow the instructions indicated in section 6.
- 7.2** CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
Forbid the entry to unauthorized persons. Keep out of reach of children. Keep away from sources of heat. If possible, avoid direct contact with sunlight. In order to avoid leakages, the containers, after use, should be closed carefully and placed in a vertical position. For more information, see section 10.
Class of store : According to current legislation.
Maximum storage period : 24. months
Temperature interval : min: 5. °C, max: 30. °C (recommended).
Incompatible materials:
Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.
Type of packaging:
According to current legislation.
Limit quantity (Seveso III): Directive 2012/18/EU:
No aplicable.
- 7.3** SPECIFIC END USES:
For the use of this product do not exist particular recommendations apart from that already indicated.



REVESTIMIENTO ELÁSTICO FOTO-RETICULABLE MACYFILM
 Code: 50450

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1

CONTROL PARAMETERS:

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

OCCUPATIONAL EXPOSURE LIMIT VALUES (TLV)

AGCIH 2014	Year	TLV-TWA ppm	mg/m3	TLV-STEL ppm	mg/m3	Remarks
4,5-dichloro-2-octyl-2H-isothiazol-3-one		-	0.060	-	0.10	Internal value
Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)		-	0.080	-	0.23	Recommended

TLV - Threshold Limit Value, TWA - Time Weighted Average, STEL - Short Term Exposure Limit.

BIOLOGICAL LIMIT VALUES:

Not established

DERIVED NO-EFFECT LEVEL (DNEL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from a occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

Derived no-effect level, workers:

- Systemic effects, acute and chronic:

Isoproturon
 4,5-dichloro-2-octyl-2H-isothiazol-3-one
 Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)

DNEL Inhalation
mg/m3

- (a) - (c)
 - (a) - (c)
 - (a) - (c)

DNEL Cutaneous
mg/kg bw/d

- (a) - (c)
 - (a) - (c)
 - (a) - (c)

DNEL Oral
mg/kg bw/d

- (a) - (c)
 - (a) - (c)
 - (a) - (c)

Derived no-effect level, workers:

- Local effects, acute and chronic:

Isoproturon
 4,5-dichloro-2-octyl-2H-isothiazol-3-one
 Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)

DNEL Inhalation
mg/m3

- (a) - (c)
 - (a) - (c)
 - (a) - (c)

DNEL Cutaneous
mg/cm2

- (a) - (c)
 - (a) - (c)
 - (a) - (c)

DNEL Eyes
mg/cm2

- (a) - (c)
 - (a) - (c)
 - (a) - (c)

Derived no-effect level, general population:

- Systemic effects, acute and chronic:

Isoproturon
 4,5-dichloro-2-octyl-2H-isothiazol-3-one
 Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)

DNEL Inhalation
mg/m3

- (a) - (c)
 - (a) - (c)
 - (a) - (c)

DNEL Cutaneous
mg/kg bw/d

- (a) - (c)
 - (a) - (c)
 - (a) - (c)

DNEL Oral
mg/kg bw/d

- (a) - (c)
 - (a) - (c)
 - (a) - (c)

Derived no-effect level, general population:

- Local effects, acute and chronic:

Isoproturon
 4,5-dichloro-2-octyl-2H-isothiazol-3-one
 Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)

DNEL Inhalation
mg/m3

- (a) - (c)
 - (a) - (c)
 - (a) - (c)

DNEL Cutaneous
mg/cm2

- (a) - (c)
 - (a) - (c)
 - (a) - (c)

DNEL Eyes
mg/cm2

- (a) - (c)
 - (a) - (c)
 - (a) - (c)

(-) - DNEL not available (without data of registration REACH).

PREDICTED NO-EFFECT CONCENTRATION (PNEC):
Predicted no-effect concentration, aquatic organisms:

- Fresh water, marine water and intermittent release:

Isoproturon
 4,5-dichloro-2-octyl-2H-isothiazol-3-one
 Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)

PNEC Fresh water
mg/l

-
 -
 -

PNEC Marine
mg/l

-
 -
 -

PNEC Intermittent
mg/l

-
 -
 -

- Wastewater treatment plants (STP) and sediments in fresh- and marine water:

Isoproturon
 4,5-dichloro-2-octyl-2H-isothiazol-3-one
 Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)

PNEC STP
mg/l

-
 -
 -

PNEC Sediments
mg/kg dry weight

-
 -
 -

PNEC Sediments
mg/kg dry weight

-
 -
 -

Predicted no-effect concentration, terrestrial organisms:

- Air, soil and effects for predators and humans:

Isoproturon
 4,5-dichloro-2-octyl-2H-isothiazol-3-one
 Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)

PNEC Air
mg/m3

-
 -
 -

PNEC Soil
mg/kg dry weight

-
 -
 -

PNEC Oral
mg/kg bw/d

-
 -
 -

(-) - PNEC not available (without data of registration REACH).



REVESTIMIENTO ELÁSTICO FOTO-RETICULABLE MACYFILM
Code: 50450

8.2 EXPOSURE CONTROLS:

ENGINEERING MEASURES:



Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction.

Protection of respiratory system: Avoid the inhalation of vapours.

Protection of eyes and face: Dispose of water taps, sources or eyewash bottles with clean water close to the working area.

Protection of hands and skin: It is recommended to dispose of water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.

OCUPATIONAL EXPOSURE CONTROLS: Directive 89/686/EEC~96/58/EC:

As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding EC marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc.), you should consult the informative brochures provided by the manufacturers of PPE.

Mask:



No, unless ventilation is insufficient. Use respiratory protection in spray applications. Use respiratory protection if there is a danger of exposure to high concentrations of emanations.

Goggles:

Advisable.

Face shield:

No.

Gloves:

Advisable. The gloves should be immediately replaced when any sign of degradation is noted.

Boots:

No.

Apron:

No.

Clothing:

No.

Thermal hazards:

Not applicable (the product is handled at room temperature).

ENVIRONMENTAL EXPOSURE CONTROLS:

Avoid any spillage in the environment. Avoid any release into the atmosphere.

Spills on the soil: Prevent contamination of soil.

Spills in water: Do not allow to escape into drains, sewers or water courses.

- Water Control Act: Este producto contiene las siguientes sustancias incluidas en la lista de sustancias prioritarias en el ámbito de la política de aguas, según la Directiva 2000/60/CE~2013/39/UE: Isoproturón, Terbutrina.

Emissions to the atmosphere: Because of volatility, emissions to the atmosphere while handling and use may result. Avoid any release into the atmosphere.

- VOC (product ready for use*): Es de aplicación la Directiva 2004/42/CE~2010/79/UE (RD.227/2006~Orden PRE/1665/2012), relativa a la limitación de emisiones de compuestos orgánicos volátiles debidas al uso de disolventes orgánicos: PINTURAS Y BARNICES (definidos en la Directiva 2004/42/CE~2010/79/UE (RD.227/2006~Orden PRE/1665/2012), Anexo I.1): Subcategoría de emisión c) Recubrimiento para paredes exteriores de sustratos minerales, en base acuosa. COV (producto listo al uso*) : 18.3* g/l* (COV máx. 40. g/l* a partir del 01.01.2010).

MATERIAL SAFETY DATA SHEET (REACH)

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830

Revision: 27/09/2016

Page 7 / 11



REVESTIMIENTO ELÁSTICO FOTO-RETICULABLE MACYFILM
Code: 50450

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1	<p>INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:</p> <p><u>Appearance</u></p> <ul style="list-style-type: none"> - Physical state : Liquid. - Colour : Colourless. - Odour : Characteristic - Odour threshold : Not available (mixture). <p><u>pH-value</u></p> <ul style="list-style-type: none"> - pH : 8.6 ± 0.4 at 20°C <p><u>Change of state</u></p> <ul style="list-style-type: none"> - Melting point : Not available - Initial boiling point : > 100* °C at 760 mmHg <p><u>Density</u></p> <ul style="list-style-type: none"> - Relative density : 1.007* at 20/4°C Relative water <p><u>Stability</u></p> <ul style="list-style-type: none"> - Decomposition temperature : Not available (technical impossibility to obtain the data). <p><u>Viscosity:</u></p> <ul style="list-style-type: none"> - Viscosity (Krebs-Stormer) : 80. ± 10. KU 20°C <p><u>Volatility:</u></p> <ul style="list-style-type: none"> - Evaporation rate : 40.4* nBuAc=100 25°C Relative - Vapour pressure : 17.5* mmHg at 20°C - Vapour pressure : 12.2* kPa at 50°C <p><u>Solubility(ies)</u></p> <ul style="list-style-type: none"> - Solubility in water : Miscible - Liposolubility : Not available (mixture untested). <p><u>Flammability:</u></p> <ul style="list-style-type: none"> - Flash point : Inflammable* °C - Autoignition temperature : Not applicable (do not support combustion). <p><u>Explosive properties:</u> Not available.</p> <p><u>Oxidizing properties:</u> Not classified as oxidizing product.</p> <p>*Estimated values based on the substances composing the mixture.</p>
9.2	<p>OTHER INFORMATION:</p> <ul style="list-style-type: none"> - Heat of combustion : 2561* Kcal/kg - VOC (supply) : 18.3 g/l <p>The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the technical data sheet of the same. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.</p>

SECTION 10 : STABILITY AND REACTIVITY

10.1	<p>REACTIVITY:</p> <p><u>Corrosivity to metals:</u> It is not corrosive to metals.</p> <p><u>Pyrophorical properties:</u> It is not pyrophoric.</p>
10.2	<p>CHEMICAL STABILITY:</p> <p>Stable under recommended storage and handling conditions.</p>
10.3	<p>POSSIBILITY OF HAZARDOUS REACTIONS:</p> <p>Possible dangerous reaction with oxidizing agents, acids, alkalis.</p>
10.4	<p>CONDITIONS TO AVOID:</p> <p><u>Heat:</u> Keep away from sources of heat.</p> <p><u>Light:</u> If possible, avoid direct contact with sunlight.</p> <p><u>Air:</u> El producto no se vé afectado por exposición al aire, pero se recomienda no dejar los recipientes abiertos.</p> <p><u>Pressure:</u> Not relevant.</p> <p><u>Shock:</u> El producto no es sensible a los choques, pero como recomendación de tipo general se deben evitar golpes y manejos bruscos, para evitar abolladuras y roturas de envases y embalajes, en especial cuando se manipula el producto en grandes cantidades, y durante las operaciones de carga y descarga.</p>
10.5	<p>INCOMPATIBLE MATERIALS:</p> <p>Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.</p>
10.6	<p>HAZARDOUS DECOMPOSITION PRODUCTS:</p> <p>As consequence of thermal decomposition, hazardous products may be produced: carbon monoxide.</p>



REVESTIMIENTO ELÁSTICO FOTO-RETICULABLE MACYFILM
Code: 50450

SECTION 11 : TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EC) No. 1272/2008-605/2014 (CLP).

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:
ACUTE TOXICITY:

Dose and lethal concentrations for individual ingredients :

Isoproturon
4,5-dichloro-2-octyl-2H-isothiazol-3-one
Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)

DL50 (OECD 401)
mg/kg oral

> 2000. Rat
756. Rat
67. Rat

DL50 (OECD 402)
mg/kg cutaneous

> 2000. Rat
680. Rabbit
140. Rat

CL50 (OECD 403)
mg/m3.4h inhalation

> 1950. Rat
> 290. Rat
> 1230. Rat

No observed adverse effect level

Not available

Lowest observed adverse effect level

Not available

INFORMATION ON LIKELY ROUTES OF EXPOSURE: Acute toxicity:

Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed
<u>Inhalation:</u> Not classified	ATE > 20000 mg/m3	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).
<u>Skin:</u> Not classified	ATE > 2000 mg/kg	-	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).
<u>Eyes:</u> Not classified	Not available	-	Not classified as a product with acute toxicity by eye contact (lack of data).
<u>Ingestion:</u> Not classified	ATE > 5000 mg/kg	-	Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).

CORROSION / IRRITATION / SENSITISATION :

Danger class	Target organs	Cat.	Main effects, acute and/or delayed
<u>Respiratory corrosion/irritation:</u> Not classified	-	-	Not classified as a product corrosive or irritant by inhalation (based on available data, the classification criteria are not met).
<u>Skin corrosion/irritation:</u> Not classified	-	-	Not classified as a product corrosive or irritant in contact with skin (based on available data, the classification criteria are not met).
<u>Serious eye damage/irritation:</u> Not classified	-	-	Not classified as a product corrosive or irritant in contact with eyes (based on available data, the classification criteria are not met).
<u>Respiratory sensitisation:</u> Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).
<u>Skin sensitisation:</u> Not classified	-	-	Not classified as a product sensitising by skin contact (based on available data, the classification criteria are not met).

- Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one, mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1). May produce an allergic reaction.

ASPIRATION HAZARD:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed
<u>Aspiration hazard:</u> Not classified	-	-	Not classified as a product hazardous by aspiration (based on available data, the classification criteria are not met).

SPECIFIC TARGET ORGANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Not classified as a dangerous product for target organs (based on available data, the classification criteria are not met).

CMR EFFECTS:

Carcinogenic effects: Is not considered as a carcinogenic product.

Genotoxicity: Is not considered as a mutagenic product.

Toxicity for reproduction: Do not harm fertility. Do not harm the fetus developing.

Effects via lactation: Not classified as a hazardous product for children breast-fed.

MATERIAL SAFETY DATA SHEET (REACH)

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830

Revision: 27/09/2016

Page 9 / 11

**REVESTIMIENTO ELÁSTICO FOTO-RETICULABLE MACYFILM**
Code: 50450**DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:**Routes of exposure: Not available.Short-term exposure: Not available.Long-term or repeated exposure: Not available.**INTERACTIVE EFFECTS:**

Not available.

INFORMATION ABOUT TOXICOKINETICS, METABOLISM AND DISTRIBUTION:Dermal absorption: Not available.Basic toxicokinetics: Not available.**ADDITIONAL INFORMATION:**

Not available.

SECTION 12 : ECOLOGICAL INFORMATION

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EC) No. 1272/2008~605/2014 (CLP).

12.1 TOXICITY:Acute toxicity in aquatic environment

for individual ingredients :

Isoproturon

4,5-dichloro-2-octyl-2H-isothiazol-3-one

Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)

CL50 (OECD 203)

mg/l.96hours

30. Fishes

0.0078 Fishes

0.19 Fishes

CE50 (OECD 202)

mg/l.48hours

5.3 Daphnia

0.0097 Daphnia

0.16 Daphnia

CE50 (OECD 201)

mg/l.72hours

0.030 Algae

0.025 Algae

0.018 Algae

No observed effect concentration

Not available

Lowest observed effect concentration

Not available

12.2 PERSISTENCE AND DEGRADABILITY:

Not available.

Aerobic biodegradation

for individual ingredients :

Isoproturon

4,5-dichloro-2-octyl-2H-isothiazol-3-one

Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)

DQO

mgO2/g

3490.

%DBO/DQO5 days 14 days 28 days
~ 30.Biodegradability

Not easy

Not easy

Inherently

12.3 BIOACCUMULATIVE POTENTIAL:

Not available.

Bioaccumulation

for individual ingredients :

Isoproturon

4,5-dichloro-2-octyl-2H-isothiazol-3-one

Mixture CIT EC 247-500-7 MIT EC 220-239-6 (3:1)

logPow

2.87

3.59

-0.830

BCF

L/kg

36. (calculated)

108. (calculated)

3.2 (calculated)

Potential

Low

High

No bioaccumulable

12.4 MOBILITY IN SOIL:

Not available.

12.5 RESULTS OF PBT AND VPVB ASSESMENT: Annex XIII of Regulation (EC) no. 1907/2006:

Does not contain substances that fulfill the PBT/vPvB criteria.

12.6 OTHER ADVERSE EFFECTS:Ozone depletion potential: Not available.Photochemical ozone creation potential: Not available.Earth global warming potential: Not available.Endocrine disrupting potential: Not available.**SECTION 13 : DISPOSAL CONSIDERATIONS****13.1 WASTE TREATMENT METHODS:** Directive 2008/98/EC~Regulation (EU) no. 1357/2014:

Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose of at an authorised waste collection point. Waste should be handled and disposed of in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8.

Disposal of empty containers: Directive 94/62/EC~2005/20/EC, Decision 2000/532/EC~2014/955/EU:

Emptied containers and packaging should be disposed of in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of emptying of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself.

Procedures for neutralising or destroying the product:

Authorised landfill in accordance with local regulations.

MATERIAL SAFETY DATA SHEET (REACH)

In accordance with Regulation (EC) No. 1907/2006 and Regulation (EU) No. 2015/830

Revision: 27/09/2016

Page 10 / 11

**REVESTIMIENTO ELÁSTICO FOTO-RETICULABLE MACYFILM**
Code: 50450**SECTION 14 : TRANSPORT INFORMATION**

14.1	<u>UN NUMBER:</u> Not applicable
14.2	<u>UN PROPER SHIPPING NAME:</u> Not applicable
14.3 14.4	<u>TRANSPORT HAZARD CLASS(ES) AND PACKING GROUP:</u> <u>Transport by road (ADR 2015) and</u> <u>Transport by rail (RID 2015):</u> Not reglamented <u>Transport by sea (IMDG 37-14):</u> Not reglamented <u>Transport by air (ICAO/IATA 2015):</u> Not reglamented <u>Transport by inland waterways (ADN):</u> Free.
14.5	<u>ENVIRONMENTAL HAZARDS:</u> Not applicable (not classified as hazardous for the environment).
14.6	<u>SPECIAL PRECAUTIONS FOR USER:</u> Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are in a vertical position and sure.
14.7	<u>TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE:</u> Not applicable.

SECTION 15 : REGULATORY INFORMATION

15.1	<u>EU SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC:</u> The regulations applicable to this product generally are listed throughout this material safety data sheet. <u>Restrictions on manufacture, placing on market and use:</u> See section 1.2 <u>Control of the risks inherent in major accidents (Seveso III):</u> See section 7.2 <u>Tactile warning of danger:</u> Not applicable (the classification criteria are not met). <u>Child safety protection:</u> Not applicable (the classification criteria are not met). <u>VOC information on the label:</u> Contains VOC max. 19. g/l - The limit value 2004/42/CE-IIA cat. c) for the product ready for use is VOC max. 40. g/l (2010). <u>OTHER REGULATIONS:</u> Not available
15.2	<u>CHEMICAL SAFETY ASSESSMENT:</u> For this mixture has not been carried out a chemical safety assessment.



REVESTIMIENTO ELÁSTICO FOTO-RETICULABLE MACYFILM
 Code: 50450

SECTION 16 : OTHER INFORMATION
16.1 TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3:

Not applicable.

ADVISES ON ANY TRAINING APPROPRIATE FOR WORKERS:

It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of material safety data sheets and labelling of products as well.

MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:

- European Chemicals Agency: ECHA, <http://echa.europa.eu/>
- Access to European Union Law, <http://eur-lex.europa.eu/>
- Threshold Limit Values, (AGCIH, 2014).

ABBREVIATIONS AND ACRONYMS:

List of abbreviations and acronyms that can be used (but not necessarily used) in this material safety data sheet:

- REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
- DSD: Dangerous Substances Directive.
- DPD: Dangerous Preparations Directive.
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations.
- CLP: European regulation on Classification, Labelling and Packaging of substances and chemical mixtures.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- ELINCS: European List of Notified Chemical Substances.
- CAS: Chemical Abstracts Service (Division of the American Chemical Society).
- UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials).
- SVHC: Substances of Very High Concern.
- PBT: Persistent, bioaccumulable and toxic substances.
- vPvB: Very persistent and very bioaccumulable substances.
- VOC: Volatile Organic Compounds.
- DNEL: Derived No-Effect Level (REACH).
- PNEC: Predicted No-Effect Concentration (REACH).
- LD50: Lethal dose, 50 percent.
- LC50: Lethal concentration, 50 percent.
- UN: United Nations Organisation.
- ADR: European agreement concerning the international carriage of dangerous goods by road.
- RID: Regulations concerning the international transport of dangerous goods by rail.
- IMDG: International Maritime code for Dangerous Goods.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.

MATERIAL SAFETY DATA SHEET REGULATIONS:

Material Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Annex of Regulation (EU) No. 2015/830.

HISTORY:
Revision:

Version: 2 21/09/2016
 Version: 3 27/09/2016

Modifications with respect to the previous Material Safety Data Sheet:

The possible legislative, contextual, numerical, methodological and normative changes with respect to the previous version are highlighted in this Material Safety Data Sheet by a mark # in red and italic.

The information of this Material Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Material Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.